

DECLARATION OF PERFORMANCE

Version 1

Unique identification code of product type

P0009 Bostik PU 2637

Intended use of construction product

EN 15651-1: F EXT- INT

Sealant for facade for interior and exterior application

Manufacturer

Bostik AB, Box 903, SE-251 09 Helsingborg, Sweden

System or systems of assesment and verification of consistancy of performance of the construction product

System 3

System 3 for reaction to fire

Harmonized standard

A notified testing laboratory, SKZ - TeConA GmbH, (1213), has performed the determination of the product-type on the basis of ITT under system 3 and performed fire tests according to systems 3 and issued corresponding test report.

Declared performance

EN 15651-1: F EXT-INT

Conditioning:

Method B

Substrate:

Mortar – M1 with primer

Väsentliga egenskaper/Väsentlige egenskaber/Perusominaisuudet/Essential characteristics	Prestanda/Ydeevne/Ytelse/Suoritustaso/Performance	Harmoniserad teknisk specifikation / Yhdenmukaistetut tekniset eritelmät/Harmonised Technical Specification
Brandklass/ Brandklasse/ Brannklasse/ Paloluokka/ Reaction to fire	E	EN 15651-1:2012
Frigörande av farliga ämnen/ Afgivelse af farlige stoffer/ Ei vaarallisia aineita/ Release of hazardous substances	NPD	Se säkerhets databladet/ Se sikkerhedsdatablad/ Katso Käyttöturvallisuustiedote/ See material safety data sheet
Vatten- och lufttätthet / Vand -og lufttæthed / Vann- og lufttetthet / Vesi- ja ilmatiiviys / Water and air tightness		
Flytmotstånd/ Flydemotstand/ Flytmotstand/ Valuma/ Resistance to flow	< = 3mm	EN 15651-1:2012
Volymförlust/ Volumensvind/ Volumtap/ Tilavuuskutistuma/ Loss of volume (%)	< = 10%	EN 15651-1:2012
Hållfasthetsegenskaper / Styrkeegenskaber / Holdbarhetsegenskaper / Pitävyysominaisuudet / Tensile properties		
Expanderat läge med vattenbegjutning/ Ekspanderet tilstand med vandbefugtning/ Ekspanderet tilstand med vannåke/ Laajentuma vesisäilytyksen jälkeen/ Elongation at break at maintained extension after water immersion	NF	EN 15651-1:2012
Hållbarhet/ Holdbarhed/ Holdbarhet/ Kestävyyt/ Durability	PASS	EN 15651-1:2012

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

A handwritten signature in blue ink, appearing to be 'Mats Ekström', written in a cursive style.

Mats Ekström - CEO
Helsingborg 2014-10-20