



Akrit 12

Wear-resistant washable semi-matt wall paint

- ✓ Can be tinted into over 30,000 colours
- ✓ Resistant to frequent cleaning
- ✓ Contains components that help remove dirt easily



Description	
Properties	<p>Acrylate water-borne paint providing maximum application comfort and resulting in wear-resistant surfaces.</p> <ul style="list-style-type: none"> ✓ Covers the surface well ✓ High decorative properties: smooth coating with semi-matt gloss ✓ Stable gloss at different light angles, including sidelight ✓ The surface is abrasion-resistant and can withstand frequent wet cleaning ✓ Contains components that help remove impurities from the painted surface easily ✓ The paint does not give off harmful substances into the air and has been classified as emission class M1 ✓ Suitable for sensitive and allergic people <p>Maximum permissible VOC content for the product (subcat. a): 30g/L; maximum VOC content in the product: ≤ 15 g/L.</p> <p>Gloss:</p> <ul style="list-style-type: none"> • semimatt (approximately 12) in accordance with EN 13300 • group 4 in accordance with RYL 2012 <p>Wash resistance:</p> <ul style="list-style-type: none"> • class 1 in accordance with EN 13300 • group 314 of painting regulations in accordance with RYL 2012 <p>Indoor load class:</p> <ul style="list-style-type: none"> • RL 05 Special loads and requirements in damp indoor spaces according to RYL 2012
Purpose	<p>Painting walls and ceilings in rooms with high performance requirements and where frequent wet cleaning is required: residential and office rooms, children's rooms, entrance halls, corridors, stair wells, public spaces, garages, workshops, cafes, restaurants, stores, clubs, etc. Is not suitable for application on floors, doors and furniture.</p>
Types of surfaces for painting	<p>New or previously painted surfaces made of concrete, aerated concrete, gypsum board, primed wood chipboard or wood fibre board; brick, surfaces filled with putty and plastered and surfaces covered with glass fibre wallpaper or other paintable finishing materials.</p>

Quality standards and labels	<ul style="list-style-type: none"> ✓ EN 13300 [Paints and varnishes. Water-borne coating materials and coating systems for interior walls and ceilings. Classification] – classification standards of coverage, gloss level and wet abrasion resistance parameters for water-borne coating materials for interior walls and ceilings ✓ ISO 11 998 [Paints and varnishes -- Determination of wet-scrub resistance and cleanability of coatings], ISO 2813 [Paints and varnishes -- Determination of specular gloss of non-metallic paint films at 20 degrees, 60 degrees and 85 degrees] – techniques for measuring gloss and wear resistance parameters. ✓ RYL – construction quality standard for finishing commonly followed in the EU area; describes coating materials, using generally accepted standards, for proper quality assurance in construction ✓ VOC (volatile organic compounds) – content in accordance with the European Union directive 2004/42/CE ✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018 ✓ “Eesti Allergialiit tunnustab” (“Estonian Allergy and Asthma Federation recognizes”) is assigned to products that are safe, reliable, do not contain fragrance or generally irritating or sensitising substances and that help to reduce indoor air pollutant levels and are suitable for people with sensitive skin or suffering from allergic diseases
Product specifications	
Surface preparation before painting	<p>Previously unpainted surfaces: Clean the surface, removing dirt and dust. Apply a suitable putty from the FILLER line: Face Filler (deep cracks), Aqua Filler (wet rooms), Fine Filler and Fine Pro Filler (finishing). Sand the filled surface to make it even and remove sanding dust. Prime filled, porous or unevenly porous surfaces with Aquastop or Tiefgrund moisture barrier. Follow the product instructions for use. Prime the surfaces with water-borne priming paint Flat to even out the surface absorption capacity, increase the durability of the painted surface and decrease the consumption of the top coat paint.</p> <p>Previously painted surfaces: The painted surface must be cleaned from loose and peeling material, grease, dust and other impurities. If mould removal is necessary, use Biotol E or Biotol Spray (follow the product instructions for use). To clean the surfaces that are very dirty or have soot, water, nicotine or grease stains, wash the surface with a soft sponge or cloth approximately 48 hours after paint application. We recommend using water and neutral or medium alkaline detergents (pH below 9). Do not use organic solvents, abrasive cleansers and hard scrubbing brushes or sponges. Extensive rubbing may make the surface glossy. We recommend using Biotol E and Biotol Spray to remove mould. Please follow the product application manual.</p>
Application	Stir the paint thoroughly before application. The paint can be diluted with water in the amount of up to 5% of its volume for the application of the first coat. Apply 2 coats with a roller or spray gun at the temperature between 10 °C and 25 °C and relative humidity not exceeding 80%. Avoid application in draughty places and at high air temperature (over +25 °C). When painting, make sure to keep a wet edge.
Care for the painted surface	The coating reaches its peak wear resistance in about 4 weeks; in the meantime, treat the surface with care until its hardness and wear resistance have reached their peak levels. If necessary, the surface can be lightly wiped with a soft sponge or cloth approximately 48 hours after paint application. We recommend using water and neutral or medium alkaline detergents (pH below 9). Do not use organic solvents, abrasive cleansers and hard scrubbing brushes or sponges. Extensive rubbing may make the surface glossy. We recommend using Biotol E and Biotol Spray to remove mould. Please follow the product application manual.
Colour	White
Dilution	The product is ready for use. The paint can be diluted with water in the amount of up to 5% of its volume.
Tinting	Machine tinting according to the Eskarocolor system (bases A, TR).
Consumption	6-10 m ² /L
Thinner	Water
Drying time	At the temperature of +20 °C and the relative humidity of 50%, the coat dries and the surface is ready for the application of another coat in 2 hours. If the temperature is lower and the humidity is higher, the drying takes longer accordingly.
Tools	Roller (pile length: 10-14 mm), airless spray gun (nozzle: 0.021–0.027"), brush
Tool cleaning	Wash with soap and water after completing work.
Additional information	
Frost resistance	None
Storage conditions	Store and transport in intact containers at the temperature between +5°C and +30°C. Protect from exposure to freezing and direct sunlight.
Safety precautions	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Keep out of reach of children. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products. In case of paint contact with eyes, wash the eyes with plenty of water.
Waste treatment	Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Waste treatment methods: code 08 01 12- Waste paint and varnish other than those mentioned in 08 01 11, waste class (Regulation (EU) No 1357/2014): non-dangerous.

Density	1,2 kg/.
Volume/weight:	0,95 L – 2,85 L –4,75 L - 9,5 L – 19 L
<p>The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: http://eskarogroup.com/contact-us</p>	